



Gateway MC-2 Cabinet

Customized Cabinets for
Outside Plant Applications

This cabinet is a pad mounted outdoor telecommunications equipment cabinet with two equipment mounting bays. Each bay includes a stationary standard EIA rack that is adjustable between 19 and 23 inches in the rear of the cabinet and a swing out (19 or 23 inch) rack towards the front. Total rack space available in the cabinet is 118U. The stationary racks have 31 U (1.75" EIA) of rack space and the swing out racks have 28 U of rack space. The right side bay is provided for AC electrical distribution and thermostat controls for the HVAC equipment.



Product Highlights

- Two ton air condition provided (other capacities available)
- 5 KW heater insures a minimum cabinet temperature of 40° F
- 48 VDC emergency cooling fans are mounted under the roof to activate in case of a power failure
- Two sliding battery drawers, holding four 100 Amp hour batteries, each located under the equipment bays
- Removable eye hooks for ease in installation
- Door latches can be padlocked for security
- Options include alarm circuits available to report
 - High temperature
 - Low temperature
 - Intrusion
 - Power Loss



Product Specifications

- Dimensions: 76" H x 74" W x 36.5" D (air conditioner adds to width)
- Aluminum construction with powder coat painted finish
- Designed to NEMA 3R requirements (NEMA 4 designs available)